Amendments to the Claims

This listing of claims will replace all prior versions, and listings, of claims in the application:

Listing of Claims:

- 1-12. (Canceled)
- 13. (Original) A process for producing synthesis gas comprising:

passing a hydrocarbon containing gas and an oxygen containing gas over a partial oxidation catalyst, under conditions effective to produce a gas stream comprising hydrogen and carbon monoxide,

wherein the partial oxidation catalyst comprises a catalytic metal and a support material;

wherein the partial oxidation catalyst includes a plurality of discrete structures, each comprising a core containing said support material and an outer region disposed on said core;

wherein the plurality of discrete structures has an average size greater than 0.5 mm; wherein the outer region has an thickness of not more than 200 microns, and further wherein more than 60% of the catalytically active metal loaded on the discrete structure is located in the outer region.

- 14. (Original) The process according to claim 13 wherein the catalytic metal comprises a Group VIII metal or noble metal.
- 15. (Original) The process according to claim 13 wherein the catalytic metal comprises rhodium.
- 16. (Original) The process according to claim 15 wherein the catalytic metal comprises about 1 wt % or less of the total catalyst weight.
- 17. (Original) The process according to claim 15 wherein the catalytic metal comprises about 0.75wt % or less of the total catalyst weight.

- 18. (Original) The process according to claim 13 wherein 80% of the catalytic metal is located within the outer region.
- 19. (Original) The process according to claim 13 wherein the outer region thickness is no greater than 100 microns.
- 20. (Original) The process according to claim 13 wherein the support material comprises alumina.
- 21. (Original) The process according to claim 13 wherein the partial oxidation catalyst exhibits a methane conversion of greater than or equal to 80 mole %.
- 22. (Original) The process according to claim 13 wherein the partial oxidation catalyst exhibits a hydrogen selectivity of greater than or equal to 80 mole %.
- 23. (Original) The process according to claim 13 wherein the partial oxidation catalyst exhibits a carbon monoxide selectivity of greater than or equal to 80 mole %.
- 24. (Original) The process according to claim 13 wherein the hydrocarbon containing gas and an oxygen containing gas over the catalyst is done at a GHSV greater then 100, 000 hr⁻¹.
- 25. (Original) The process according to claim 13 wherein the hydrocarbon containing gas comprises methane.
- 27-29. (Canceled)
- 30. (Currently amended) The process according to claim [[25]] 13 wherein 80% of the catalytic metal is located within the outer region.
- 31-43. (Canceled)
- 44. (New) The process according to claim 13 wherein the catalytically active metal is iridium, rhenium, or rhodium.
- 45. (New) The process according to claim 44 wherein the catalytically active metal comprises

about 1 wt % or less of the total catalyst weight.

- 46. (New) The process according to claim 44 wherein the catalytically active metal comprises about 0.75 wt % or less of the total catalyst weight.
- 47. (New) The process according to claim 44 wherein the catalytically active metal comprises about 0.5 wt % or less of the total catalyst weight.
- 48. (New) The process according to claim 15 wherein the catalyst further comprises a promoter selected from the group consisting of lanthanide metals, rhenium, zirconium, and combinations thereof.
- 49. (New) The process according to claim 15 wherein the catalyst further comprises a promoter selected from the group consisting of rhenium, zirconium, and combinations thereof.
- 50. (New) The process according to claim 15 wherein the catalytic metal comprises about 0.5 wt % or less of the total catalyst weight.
- 51. (New) The process according to claim 13 wherein the outer region is delimited by the exterior surface of the catalyst structure; the core comprises the center of the structure; and wherein the catalyst comprises a gradient in catalytically active metal concentration with the highest concentration near said exterior surface and essentially zero near said center.
- 52. (New) The process according to claim 13 wherein the outer region comprises rhodium and a promoter selected from samarium, rhenium, zirconium, and combinations thereof.
- 53. (New) The process according to claim 13 wherein the catalyst further comprises a promoter, and more than 60% of the promoter loaded on the discrete structure is located in the outer region.
- 54. (New) The process according to claim 13 wherein more than 80% of the catalytic metal is located within the outer region.
- 55. (New) The process according to claim 13 wherein the outer region is a catalytic outer

layer greater than 0.5 micron thick.

- 56. (New) The process according to claim 13 wherein the catalyst further comprises a substantially blocked-micropore layer disposed between the outer region and the center of the core, said substantially blocked-micropore layer being either at the periphery of the core or extended substantially throughout the core.
- 57. (New) The process according to claim 56 wherein the catalyst further comprises a substantially blocked-micropore layer disposed at the periphery of the core.
- 58. (New) The process according to claim 56 wherein the substantially blocked-micropore layer is created before the loading of the catalytically active metal by a method comprising applying silicic acid or sodium carbonate to the support material and then calcining.
- 59. (New) The process according to claim 13 wherein the core is nonmicroporous.
- 60. (New) The process according to claim 59 wherein the nonmicroporous core is created before the loading of the catalytically active metal by applying a pore blocking material to the support material and then calcining, said pore blocking material being selected from the group consisting of silicic acid and sodium carbonate.
- 61. (New) The process according to claim 13 wherein the discrete structures are particles with a trilobe configuration.
- 62. (New) The process according to claim 13 wherein the discrete structures are particles with a spherical configuration.
- 63. (New) The process according to claim 13 wherein the discrete structures are particles having a size greater than about 1 mm.
- 64. (New) The process according to claim 13 wherein the support material comprises a refractory material selected from the group consisting of alumina, titania, zirconia, gallium oxide (Ga₂O₃), silica and mixtures thereof.

Appl. No. 10/747,718 Response dated June 27, 2006

Reply to Office Action of June 6, 2006

65. (New) The process according to claim 13 wherein the oxygen containing gas comprises

air, oxygen-enriched air, oxygen blended with a diluent gas, or substantially pure oxygen.

66. The process according to claim 13 wherein the hydrocarbon containing gas comprises

natural gas.

67. (New) The process according to claim 13 wherein the partial oxidation catalyst exhibits a

hydrogen selectivity of greater than or equal to 85 mole %.

68. (New) The process according to claim 13 wherein the partial oxidation catalyst exhibits a

carbon monoxide selectivity of greater than or equal to 85 mole %.

69. (New) The process according to claim 13 wherein the partial oxidation catalyst exhibits a

methane conversion of greater than or equal to 85 mole %.

70. (New) The process according to claim 13 wherein the gas stream comprising hydrogen

and carbon monoxide is further reacted in a hydrocarbon synthesis reactor under conditions

effective to produce liquid hydrocarbons.